

Specifications

HP Quick Connect Series Performance Data

Model Number	Capacity gal / liter	Maximum Operating Pressure psi / kPa / Bar	Drawdown 30/50 Setting* gal / liter	Diameter* inch / cm	Overall Height* inch / cm	Inlet/Outlet to floor inch / cm	System Connection Top Bottom	Assembly Weight* lb / kg	Pallet Qty.
HP-7 / WM-110	30 / 114	75 / 500 / 5.0	6.6 / 25.0	16 / 41	43 3/4 / 111	1 1/2 / 3.8	1/4" vent line NPT Socket	26 / 11.8	9
HP-9 / WM-150	40 / 151	75 / 500 / 5.0	9.0 / 34.1	16 / 41	56 1/2 / 144	1 1/2 / 3.8	1/4" vent line NPT Socket	29 / 13.2	9
HP-8SQ / WM-150SQ	40 / 151	75 / 500 / 5.0	8.0 / 30.3	21 / 53	35 1/4 / 90	2 / 5.1	1/4" vent line NPT Socket	34 / 15.4	4
HP-18 / WM-300	80 / 303	75 / 500 / 5.0	17.8 / 67.4	21 / 53	62 / 157	2 / 5.1	1/4" vent line NPT Socket	44 / 20.0	N/A
HP-26 / WM-450	120 / 454	75 / 500 / 5.0	25.5 / 96.5	24 / 61	72 1/2 / 184	2 / 5.1	1/4" vent line NPT Socket		