

Specifications

HP Quick Connect Series Performance Data

Model Number	Capacity gal / liter	Maximum Operating Pressure psi / kPa / Bar	Drawdown 30/50 Setting* gal / liter	Diameter* inch / cm	Overall Height* inch / cm	Inlet/Outlet to floor inch / cm	System Connection Top Bottom	Assembly Weight* lb / kg	Pallet Qty.
HP-7 / WM-110	30 / 114	75 / 500 / 5.0	6.6 / 25.0	16 / 41	43 3/4 / 111	1 1/2 / 3.8	1/4" vent line NPT Socket	26 / 11.8	9
HP-9 / WM-150	40 / 151	75 / 500 / 5.0	9.0 / 34.1	16 / 41	56 1/2 / 144	1 1/2 / 3.8	1/4" vent line NPT Socket	29 / 13.2	9
HP-8SQ / WM-150SQ	40 / 151	75 / 500 / 5.0	8.0 / 30.3	21 / 53	35 1/4 / 90	2 / 5.1	1/4" vent line NPT Socket	34 / 15.4	4
HP-18 / WM-300	80 / 303	75 / 500 / 5.0	17.8 / 67.4	21 / 53	62 / 157	2 / 5.1	1/4" vent line NPT Socket	44 / 20.0	N/A
HP-26 / WM-450	120 / 454	75 / 500 / 5.0	25.5 / 96.5	24 / 61	72 1/2 / 184	2 / 5.1	1/4" vent line NPT Socket	64 / 29.0	N/A

Note: Maximum external operating temperature 120°F (49°C). Maximum internal operating temperature 100°F (38°C). Minimum operating temperature 40°F (4°C).

* Diameter, height and weight may vary slightly without notice.

** In keeping with current industry standards, drawdown factors are based on Boyle's law. Actual drawdowns will vary depending upon system variables, including the accuracy and operation of the pressure switch and gauge and operating temperature of the system.